

Product Code	Description	Weight	Air Permeability	Air Permeability	Initial Pressure Drop	Filtration Class	Roll Length
		gr/m2	Cfm @125pa	l/m ² .s @200pa	pa	EN779:2012 / EN1822 / ISO 16890 / EN149 / NIOSH 42 CFR 84 / EN14683	mt

Industrial Dust Collection / APC - Surface-loading

HF-B115-FR-07	80/20 Blend Corrugated / Nano / FR	115	36	290	70	F7	1150
HF-B115-FR-08	80/20 Blend Corrugated / Nano / FR	115	31	250	80	F8	1150
HF-B115-FR-09	80/20 Blend Corrugated / Nano / FR	115	26	210	95	F9	1150
HF-B115-FR-11	80/20 Blend Corrugated / Nano / FR	115	16	125	85	E11 @ 0.2-0.3 µm	1150
HF-B122-FR-07	80/20 Blend Corrugated / Nano / FR	122	23	187	107	F7	1150
HF-B122-FR-09	80/20 Blend Corrugated / Nano / FR	122	21	170	120	F9	1150
HF-SR250-FR-09	Bico PET / Nano / FR	250	9	75	260	F9	350
HF-SR250-FR-10	Bico PET / Nano / FR	250	12	95	110	E10 @ 0.2-0.3 µm	350
HF-SR250-FR-11	Bico PET / Nano / FR	250	7	60	180	E11 @ 0.2-0.3 µm	350
HF-SR250-FR-12	Bico PET / Nano / FR	250	5	40	265	E12 @ 0.2-0.3 µm	350
HF-SRC260-09-AS	Bico PET / Nano / Antistatic	260	18	145	140	F9	350

See All Product +

The values are for information purposes, the target values are stated in the product TDS

*All data and statements concerning these products may be considered as being indicative of representative properties obtainable. We make no warranty, expressed or implied, concerning actual use or results because of industry specific influenc



Açık Kart Bilgi Teknolojileri Ticaret A.Ş

+90 258 251 5057

www.hifyber.com

sales@hifyber.com